

## Technical data sheet

Adhesive glue. Fast drying.

Bonding compound for fixing plasterboards and composite boards to different types of supports, when carrying out direct coverings.

It should also be used as a filler for separations greater than 3mm that may occur in the joints between plates. It is not suitable for any phase of joint treatment with or without tape.

### Application areas:

All type of interior dry construction, such as: partition and wall systems, wall lining systems, suspended ceilings, lighting and pelmet features and other decorative applications. Suitable for use in wet areas.



### Technical data:

Setting time	2h30' – 4h
Usage time once mixed	Approximately 3 hours, depends on the conditions of use.
Conditions of use	Between 5° and 35°C, <85% HR
Mixing ratio (water / product)	10 liters / 20 kg bag
Reaction to fire	A1
Approximate consumption* * Approximate consumption per m <sup>2</sup> of direct coating on an irregular support, less than 20mm, and without waste	5kg/m <sup>2</sup>
Application type	Manual

### Standards:

- EN 14496.
- CE Marking.

### Storage and use:

Up to 12 months in unopened original packaging, protected from moisture. Store the material on flat surfaces protected from humidity and sun. Extreme humidity, cold or heat accelerate aging and can change the behavior of the dough. Do not store in direct contact with the ground.

### Handling:

It is advisable to wear a protective mask and gloves.