

## Technical data sheet

Joint Filler. Fast drying.

Paste for the complete treatment, filling and finishing of joints and treatment of screw heads in laminated plasterboard systems, with joint tape.

### Application areas:

All type of interior dry construction, such as: partition and wall systems, wall lining systems, suspended ceilings, lighting and pelmet features and other decorative applications. Suitable for use in wet areas.



### Technical data:

Setting time	1h45' – 2h30'
Usage time once mixed	Approximately 2 hours, depends on the conditions of use.
Conditions of use	Between 5° and 35°C, <85% HR
Mixing ratio (water / product)	10 liters / 20 kg bag
Reaction to fire	A1
Type of paste (according to EN13963)	3B
Approximate consumption * * Approximate consumption per m2 of direct coating on an irregular support, less than 20mm, and without waste	Q1=0,23kg/m <sup>2</sup> , Q2=0,29kg/m <sup>2</sup> , Q3=0,32kg/m <sup>2</sup>

### Standards:

- EN 14496.
- CE Marking.

### Storage and use:

Up to 12 months in unopened original packaging, protected from moisture. Store the material on flat surfaces protected from humidity and sun. Extreme humidity, cold or heat accelerate aging and can change the behavior of the dough. Do not store in direct contact with the ground.

### Handling:

It is advisable to wear a protective mask and gloves.