

Technical data sheet

Joint Filler. Normal drying.

Paste for the complete treatment, filling and finishing of joints and treatment of screw heads in laminated plasterboard systems, with joint tape. It can be used as a general barrier for surfaces with imperfections and small irregularities. It is recommended for manual or mechanical use. Not suitable for treating joints without tape.



Application areas:

All type of interior dry construction, such as: partition and wall systems, wall lining systems, suspended ceilings, lighting and pelmet features and other decorative applications. Suitable for use in wet areas.

Technical data:

Drying	12 to 48 hours
Usage time once mixed	It is not recommended to use after 48 hours. If the dough is prepared, store it in a closed, covered container. It is recommended to cover the surface of the mixture with a thin layer of water or polyethylene film.
Conditions of use	Between 5° and 35°C, <85% HR
Mixing ratio (water / product)	9 liters / 20 kg bag
Reaction to fire	A2-s1, d0
Type of paste (according to EN13963)	3A
Approximate consumption* * Approximate consumption per m ² of board with thinned edge, without taking into account perimeter joints and without waste.	Q1=0,25kg/m ² , Q2=0,30kg/m ² , Q3=0,34kg/m ²

Standards:

- EN 13963.
- CE Marking.

Storage and use:

Up to 12 months in unopened original packaging, protected from moisture. Store the material on flat surfaces protected from humidity and sun. Extreme humidity, cold or heat accelerate aging and can change the behavior of the dough. Do not store in direct contact with the ground.

Handling:

It is advisable to wear a protective mask and gloves.